

Specifications

- Double-Coated Foam Tape System: closed cell, cross-linked polyethylene foam coated on both sides with a synthetic rubber adhesive.
- For use in mounting signs, wire clips, moldings, reflectors, molded and extruded plastics, hardware, etc.
- Moderate tack and excellent shear and adhesion to most surfaces
- Foam carrier provides gap filling for bonding to irregular surfaces
- Closed cell foam does not absorb water
- Available in 1/32", 1/16" and 1/8" thicknesses

Physical Properties

Physical Property	Test Method	Unit	Value
Peel Adhesion	PSTC 101	Oz/in	160
Shear Adhesion: Air Side	PSTC 107 (modified)	Days to Fail	14+
Shear Adhesion: Liner Side	PSTC 107 (modified)	Days to Fail	14+
Service Temperature		°F	30 to 150
Application Temperature		°F	68 to 100
Color			White

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.