

Specifications

- Compressible foam sealant
- Molds to irregular surfaces
- Expands and conforms to fill gaps
- Resists vibrations, jolts and shock
- Resists ozone and UV degradation
- Won't dry out or crack

Physical Properties

Physical Property	Test Method	Value
Raw Material Base		Polyurethane Foam
Color		Black
Specific Gravity		0.010 - 0.20
Elongation	ASTM D 412	<200%
Odor		Odorless
Solids by Weight		100%
QUV Exp.		No Effect
Max. Temperature	°F	180
Physical State		Saturated Open Cell foam
Shelf Life		20 Years

Acrylic Adhesive with 72# Poly Coated Kraft Liner

Physical Property	Value
180° Peel: 30 min. dwell on SS	120 oz/in
Loop Tack	9 lbs.
Polyken Teck: 100 g/cm ² , 1 sec dwell, 0.1 cm/sec separation rate	800 grams
Shear Resistance:	1 in ² - 300+ hrs.; 1/in ² - 1 hr. (90°, 2 lbs. load)

Storage and Handling: No special handling is required for this product. Store in a cool dry area for maximum shelf life and effectiveness.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.